# Mobile Ultra-Broadband, Super Internet-of-Things and Artificial Intelligence for 6G Visions

# Hamza Ali Alshawabkeh

Department of Computer Information Systems -Al-Baha University, Al Baha, Kingdom of Saudi Arabia (KSA)

## Abstract

Smart applications based on the Network of Everything also known as Internet of Everything (IoE) are increasing popularity as network connectivity requires rise further. As a result, there will be a greater need for developing 6G technologies for wireless communications in order to overcome the primary limitations of visible 5G networks. Furthermore, implementing neural networks into 6G will bring remedies for the most complex optimizing networks challenges. Future 6G mobile phone networks must handle huge applications that require data and an increasing amount of users. With a ten-year time skyline from thought to the real world, it is presently time for pondering what 6th era (6G) remote correspondence will be just before 5G application. In this article, we talk about 6G dreams to clear the street for the headway of 6G and then some. We start with the conversation of imaginative 5G organizations and afterward underline the need of exploring 6G. Treating remote proceeding and impending organization improvement in a serious way, we expect 6G to contain three critical components: cell phones super broadband, very The Web of Things (or IoT and falsely clever (artificial intelligence). The 6G project is currently in its early phases, and people everywhere must envision and come up with its conceptualization, realization, implementation, and use cases. To that aim, this article presents an environment for Presented Distributed Artificial Intelligence as-a-Services (DAIaaS) supplying in IoE and 6G applications. The case histories and the DAIaaS architecture have been evaluated in terms of from end to end latency and bandwidth consumption, use of energy, and cost savings, with suggestion to improve efficiency.

## Keywords:

Smart Services, 6G Wireless Communication, Artificial Intelligence, Service (DAIaaS), Mobile Ultra-Broadband, Technologies.

# I. Introduction

Numerous applications, particularly superior in quality audio/video sharing, have grown accessible as a result of recent improvements in networked communications. Mobile phone use has become a crucial component of contemporary culture. It is vital to our finances, wellness, learning, and many different kinds of other organizations. Today, wireless communication networks link nearly every segment of the world's the population (S. Chen, Y.-C. 2020). Following the fruitful interconnection of billions of portable computing devices by means of wireless internet access, the primary objective of the mobile web is now shifting to the pervasive connectivity of numerous things and machines, resulting in the creation of the Worldwide Web of Things (IoT).

Mobile communications devices are often upgraded to a higher-technology version at the turn of each decade. According norms, mobile telephone networks will reach fifth generation, or 5G, in 2020,(M.H. Alsharif, 2020), the first times since the 1980s. Many consider 5G to be the peak of mobile data transmission technology. 5G and its precursor, the fourth era (4G, previously known as LTE-Progressed), are remarkable for working with the advancement of a Web of-Things, or IoT, empowered mental administrations and application-arranged eco-framework.

All the more explicitly, 5G backings a large number of conveniences, including Enhanced Mobile Broadband (eMBB), Massive Machine-Type Communications (mMTC), and Ultra-Reliable Low Latency Communications (uRLLC), (L.U. Khan, 2020), which were all intended to move beyond the restrictions of 4G.

This change has led to the development of remote interactions between humans and physical devices (S. Basharat, 2021). Such highly data-intensive telecommunications could arise in media wherein humans can engage with another person remotely via touching (haptic exchange of information) or actuation.

The upcoming 6G technologies will probably offer ultrareliable and zero latency communication, enabling applications that are vital such as unmanned aerial vehicle (UAV) remote control, transmission of information,(H. Wang, 2014), IoT interpersonal interaction, tactile internet access, smart power plants, and self-driving cars.

Ultra-Reliable and Low-Latency the communication (URLLC) equipment is becoming increasingly vital for developing sixth-generation (6G) networks. This service category is distinguished by its exacting ultra-reliability and low-latency criteria, which need an interpreting error chance of a minimum 105. URLLC provides highly

Manuscript received December 5, 2023

Manuscript revised December 20, 2023

https://doi.org/10.22937/IJCSNS.2023.23.12.25

important application support, such as UAVs, which are unmanned aerial vehicles, control information transmission, intelligent networks, tactile the worldwide web, and to help others (X. You, C.-X.2021).

Previous communication methods were throughputcentric, with the Shannon efficiency calculation assumed an indefinite blocks length. URLLC mechanisms, on the other hand, are dependable and latency-centric, and so employ the infinite block the duration capability calculation. There is research on channeled coding speed and its capacity limitations for finite interfere with length. URLLC will also be vital for vertical and time-sensitive projects like as manufacturing machinery and smart grids that demand precise time integration throughout wireless and wired nodes on the move and a reference time sources (V.-L. Nguyen, 2021).

URLLC places a premium on radio resource administration in next-generation wireless communications the networks, especially for IoT. Many URLLC IoT network research issues concentrate upon radio resource management. The advent of 5G has increased the demand for URLLC, which older networks are unable to offer due to the necessity of reaching an end-to-end latency of twenty nanoseconds or more amongst users. This delay is insufficient for more modern wireless networks such as 5G and 6G.

Data-bot, Socratic, and Fyle were just a few of the many different programs we use on a daily, if not every hour, basis. AI has helped a wider spectrum of industries, including systems for recommending goods, autonomous cars, renewable energy, agriculture, medical services, transportation, security, economics, smart towns and neighborhoods, and so on. The worldwide AI business is expected to increase to 126 billion US dollars by 2025, up from a valuation of \$10.1 billion in 2018.

By constantly tracking and reacting on data, AI enables us to integrate "smartness" in our settings (D.C. Nguyen, M. 2021). The idea of the Internet of Everything (also known as IoE) paradigm expands on the worldwide web of goods (IoT) paradigm through the integration of numerous elements in this ecosystems such as sensors, items, services, individuals, and knowledge.

The main issue with these IoE enabled intelligent locations is to create effective techniques for transferring data and positioning in these widespread surroundings, which are connected to the 4Vs of massive-data analytics volume, acceleration, variety, and validity. To serve these services and handle the issues, the network structure was going to have to be smarter.

All the more explicitly, 5G gives a large number of highlights, including worked on Portable Broadband organizations (eMBB), fantastic Machine Terminal Telecom (mMTC), and super Dependable Low Inertness Correspondence, (uRLLC), which were all intended to conquer the limits of 4G (N.- N. Dao, 2021).

For instance, 5G organizations are wanted to convey top information paces of 20 Gbps, 3x unearthly efficiency, multiple times more energy-effective activity, and a Gbps UI with a comprehensive dormancy of 1 ms when contrasted with 4G organizations. 5G will likewise give consistent connections to gadgets with 500 km/h versatility, an association thickness of 1,000,000 things/km2, and a region data transfer capacity of 10 Mbps/m2.

The 5G organizations are supposed to give a broad cluster of shrewd IoE-related administrations; in any case, this won't be sufficient to satisfy the requirements for impending brilliant settlements. Since savvy urban communities mechanize our environmental factors by making a computerized overlay on top of obsolete foundations investor request has soar.

At first, the Lead research drive for 6G would be completed with the target to mutually lay out a system for 6G development and to embrace 5G organizations. The essential objective of the 6G Lead examination is to make a civilization that is fueled by limitless and quick network remote correspondence. What's more, the South Korean government inked an arrangement with the Catholic College of Oulu in Finland to speed up the headway of 6G innovations.

LG has likewise fabricated an exploration office at the Korean Establishment of Science and Innovation to direct 6G organization based research. The Korean transporter has likewise sent off a helpful examination drive on 6G-based innovations including accomplices like Motorola, Nokia, Samsung, and Ericsson. Besides, 6G-related research activities have started in China, and Huawei has started 6G systems administration research at its Ottawa-based research office in Canada.

A few scholarly individuals are effectively taking part in research on various key parts of 6G innovation, including learning calculations, atomic Nano-gadgets, media transmission starting points for and 6G testbeds, most prominently at the NYU Remote exploratory focus.

As 5G organizations approach the business activity stage, a few significant examination foundations definitely stand out enough to be noticed on 6G organizations as of late. The 6G organizations are intended to further develop execution by offering top information rates of around 1 Tbps and very little dormancy (microseconds). Besides, as stood out from 5G organizations, the organization that utilizes 6G is supposed to increment limit by a component of 1,000 utilizing terahertz recurrence and vertical multiplexing. Through the incredible blend of satellite and undersea correspondence, the 6G organization will likewise give overall inclusion.

The 6G wireless communication technology has drawn the fascination of multiple researchers since to its wonderful and powerful attributes in different disciplines, as seen by spectacular breakthrough promotion in most sectors, and anticipates to be noticeable from 2030 onward. From 2018 till present, several nations have embarked on fascinating 6G campaigns, including Finland, the United States, China, South Korea, and Japan.

Furthermore, various scholarly and practical approaches, as well as major contributions, are currently made by researchers worldwide in the field of 6G. This is due to the obstacles and less competent structure of 5G toward current living styles, such as getting fewer supportive of immersive communication at lower rates of data, and automated surveillance and establishing of the patient's well-being (C.D. Alwis, 2021).

Intelligent technology (AI) and 6G are crucial players in spreading resources in hazardous and valuable healthcare settings. The Internet of Things, also known as the IoT, has dramatically altered the healthcare business through the use of sensors, actuators, connections, and other devices, leading to the computerized physical system (CPS)(Qi, Q.; Chen, 2020).

Due to its concentrated nature, the growing online framework is unsuitable to handle the majority of the application spectrum. For bridging that gap, a novel idea known as the online of medical objects (IoMT) was put forward in which end-users and their own private entities are foundations in the rapidly evolving online world (Liu, C.; 2020). Recent developments including 5G, edge/cloud computation, Bluetooth low-power applications energy (BLE), and IoMT networked gadgets are undergoing a revolution.

# A. Objectives

- 6G research provides far higher data speeds than 5G, perhaps in the TeraBits Per Second seconds (Tbps) area.
- Investigated several design options for DAIaaS and assisted in identifying performance constraints.

### **II. LITERATURE REVIEW**

(Padhi, P. K., 2021) Medical care applications are as of now experiencing computerized time weaknesses because of the discriminatory dissemination of wellbeing related assets, specifically in provincial spots all through the world. The mental information knowledge, which computational reasoning, coordinates huge data examination, and small clever machines, especially little AI strategies, can be used in assessing a patient's wellbeing status, both physiologically and mentally, turning the ongoing medical services framework. The intermingling of 6G empowered Touchscreen the web, mental information investigation, and Organization of Wellbeing takes into consideration the far off recognition of patients' personal states for diagnosing sicknesses. Anything is proposed to fabricate the 6GCIoHE framework, which means to give overall general openness, amazingly low idleness, high reliability, and upgraded execution in mental ailment progressively to ensure patients get ideal treatment, particularly with respect to haptic undertakings.

(Zhang, L., 2019) With a ten-year time skyline from thought to the real world, it is presently time to think about what 6th era (6G) remote correspondence will be just before fifth-age (5G) organization. In this article, we present 6G dreams that will open the street for the progression of 6G and then some. We start with an outline of state of the art 5G innovation and afterward feature the need of examining 6G. Considering existing and forthcoming remote interchanges advancement, we expect 6G to include three significant viewpoints: remote super broadband, outrageous the Web of Everything (IoT), and computational insight (artificial intelligence).

(Mistry, Z., 2021) Every day and year, wireless communication technology advances. This article addresses the upcoming wireless messaging needs and how emerging technologies aid in attaining the communication needed to go over 5th generational (5G) and 6th generations (6G) innovations, as well as their roles in various types of applications. 6G includes three major progress features: ultra-broadband cell phones, the Internet in Conditions (IOT), and artificially intelligent technology (AI). Tera hertz (THz) connectivity may essentially be utilized to accomplish super IOT, and deep learning technologies are potential AI prospects.

(Seng, K. P., 2022) Sensor, processing, and technology for communication advancements and convergence have molded today's Internet of Things. The increasing expansion of data and services needed introduces new obstacles for the Internet of Things. Innovative technologies and intelligent methodologies have the potential to play a significant role in driving the development of intelligence architectures and services in the Internet of Things, hence forming the foundation for artificial intelligence.

(Gai, R., 2021) People's ways of interacting are continually evolving as information technology continues to develop. As the most prevalent means of communication, 5G has piqued the interest of people in every aspect of life. The paper discusses the history of 5G development as well as various major 5G technologies such as Orthogonal Frequency Division multiplexing (OFDM) technology & adjustable frame design. It also discussed a few major 5G applications in the Digital Economy of Things and anticipated 6G growth options.

(Iliev, T. B., 2021) With the launch of 5G in wireless networks, researchers' attention is turning to sixth generational networks. This next generation is scheduled to completely replace the current network of 5G by the end if 2030. The use of AI is a key technology in 5G, above 5G, and future networks of 6G. Intelligence is establishing the proclivity to open up the opportunities of the 5G networks and future 6G mobile broadband networks by leveraging universal structures, open network structures, softwaredefined networking, network service virtualization in your application multi-access compute at the edge, vehicular networks, and other technological advances.

(Ndiaye, M., 2022) The International Technologies Union (ITU) regulates wireless generations, which occur every 10 years. Though research into improving the performance of the 5G networks is underway in laboratories, tests into the notion of the next mobile subsequent generations 6G have begun. The 6G, which is scheduled to be operational around ten (10) years, would address a number of difficulties, including the reach of white or underprivileged regions. THz, one of the possible ranges of frequencies for 6G, could enable a very powerful transport of details (data rates) in subsequent wireless communication systems, particularly the Internet of Things, also known as IoT, system for communication.

(Wang, Z., Du, 2022) Following the worldwide commercialization of the fifth-generation, or 5G, network, several nations, particularly China, the United States, European countries, Japan, and the Republic of Korea, have begun investigating the sixth-generation (6G) mobile data network, corresponding to the traditions of "planning the next while monetizing the current." Currently, development towards networks using 6G is in its early stages. The vision and criteria for 6G are still being researched, and the sector has yet to identify the crucial technologies that will allow for 6G. However, 6G will undoubtedly build on 5G's success. As a result, prioritizing the development of highquality 5G systems and the seamless integration of 5G into sectors before 2030, whenever 6G is expected to be went live, is critical.

(Iannacci, J. 2021) The future 6G, which is Super-Internet of Things (Super-IoT), and Tactile Internet (TI) are already posing hurdles much beyond what 5G, which is still in its early stages, will be able to do. Conventional device and network design methodologies will not completely tackle what the powered by AI (Artificial Learning) 6G connection will be. This attempt aims to initiate and promote a dialogue on unique ways for thinking about and creating Hardware-Software (HWSW) systems, with the objective of making based on artificial intelligence 6G possible.

(Zhang, C., 2021) The widespread implementation of next generation technologies for information and communication, such as AI, IoT (the Network of Things), and the technology for block chains, is accelerating the global technological and industrial change. Artificial intelligence has piqued the interest of government, industry, and academics. Popular publications on AI released in recent years are chosen and studied in this study. This research attempts to offer an overview of machine learning through business information assimilation

## **III. METHODOLOGY**

A survey of our technique as far as the main thrusts for every one of these contextual investigations, as well as the conditions, application and simulated intelligence sending models, and detecting and programming parts, is given in the paper. This section delves into the methods we use and architecture, as well as the main parts of our simulations.

*Hardware and software:* To simulate and assess DAIaaS, we utilized the iFogSim simulation program. It was chosen because it allows us to simulate a variety of applications, modules, and locations, streams of information, gauges, boundaries, fogs, and virtual datacenters as well and connections(Nazar, M.J.; 2023).

All tests are run on the Aziz machine (Jeddah, Saudi Arabia), which has 492 hubs each having 24 centers. We were equipped for to run numerous enormous models with various settings on numerous hubs all the while thanks to the PC.

In the five-layer 6GCIoHE layout, it is used at the level of processing, also known as the middleware layer. The IoHE creates a vast quantity of data, which can be kept and processed with the aid of the cloud. Medical experts can monitor a patient's health by capturing information obtained from multiple sensors and storing it in the cloud(Nazar, M.J.; 2021).

Considering the Figure 1 portrayal of a constant 6Gcellular-IoT net in which a BS having M antenna interfaces with Q Multi-modal IoT user-owned items (UEs) with each N antennae.



Fig. 1 The network architecture of the 6G-IoT connection

IoT devices ought to possess sufficient resources to do precise calculations while conversing effectively. However, supplying electrical power to a huge internet of things (IoT) network is a difficult task. Because of the substantial human cost and ecological strain, regular substitute of batteries for broad IoT is impracticable. As a result, using the WPT approach to deliver one-to-many charging by utilizing the open nature of the mobile broadcast network is practical(Qi, F.; Li, 2021). Equation (1) might be used to represent the power brought together at the qth UE.

$$e_q = \frac{U}{2} \phi_q \parallel G_q^G g \parallel^2 \dots 1$$

$$K_r = g_r \{ \sum_{q=1}^{Q} f_{q,r}(d_{q,r}) \}, r = 1, 2 \dots R \qquad \dots 2$$

$$P_T = P_{FIX} + P_t + P_c \qquad \dots 3$$

$$P_T = P_{FIX} + \sum_{n=1}^{N} \sum_{k=1}^{K} \frac{1}{n} P_{n,k} + P_S \sum_{n=1}^{N} L \qquad \dots 4$$

Consider how every deployed RRU shares data with the linked IoT devices. The enabled RRUs are somewhat stable, allowing them to be used in internet of things systems. Amplifier and RRU use power account for the majority of the total electricity used in the 6G-IoT networks.

#### A.Variance-Based Integrating of 6G Mobile IoT Model

This section provides a variance-based technique for achieving successful ECC inclusion in 6G mobile IoT. Despite having the same RF transporter, the performance metrics for both communication and the computation signals differ. For interaction, the communication signal of each IoT UE should be segregated from the mixed signals at the BS. As a result, the received signal quality, or SINR, must be high.



Fig. 2 Signal uplink transmission network block diagram for the designed VIM6G-IoT design

Each layer involves gadgets with changed asset regions, which are recreated utilizing numerous boundaries. We laid out the edges for these qualities in view of the prerequisites of contraptions that are right now accessible. The main table records every one of the classifications of contraptions and their related highlights (edge, haze, and mists gadgets).

In the reenactments, the handling capacity of these hardware are communicated by specific measures of MIPS (Million Drives each Second) and Smash, which represents irregular access memory. Uplink and downlink throughput are utilized to copy correspondence capacities. When contrasted with haze and edge gadgets, the MIPS variable for cloud for a solitary PC (VM) has the most elevated MIPS and Smash (210,000 and a 50,000-values Lyu, B.; 2021).

## **Table 1 Configurations of devices**

Device parameter	Cloud	Fog	Edge
MIPS	210,000	40,000	4000
RAM	50,000	5000	9000
Uplink bandwidth	200	10,000	10,000
Downlink	10,000	10,120	10,000
Busy power	15×102	105.256	87.59
Idle power	15×53.69	85.6991	49.98

## B.Obj Detector module.

In the IoE-6G situation, the Obj Distinguishing module is situated in the cloud, though in the IoE-Haze 6G situation, it is situated in the haze hub. It acknowledges film streams (motion\_vid\_strm) by the movement recognition module and perceives protests keenly, initiating Obj Tracker on the off chance that it hasn't been set off earlier for a similar item. How much work used in the Brilliant Camera program are recorded in Table 2 Yigitcanlar, T.;2020). We will get back to it in the wake of talking about the question. Contingent upon the conditions (IoE-6G versus IoE-Haze 6G), every module can be placed in various levels (e.g., edge, haze, or mists units).

	Source		CPU	Netw
Work	S	Destinati	Requireme	ork
load Type	modul	on	nt	(byte
	е		iit	s)
Vid ctrm	Camer	Motion	1002	าวห
via_sum	а	detector	1002	23K
	Motio			2000
Motion_v	n	Ohi D	2900	
id	detect	00_0		
	or			
Detect_o	Ohi D	User	800	2051
bj	ODJ_D	interface	000	2031
Obj_locat	Ohi D	Obj	1401	107
ion	ODJ_D	tracker	1401	197
Cam_ctrl	Obj_T	Camera ctrl	90	140

Table 2 The workload adjustment for intelligentsurveillance

The Obj Locator modules conveys two undertakings to the screen: the found article (detected\_obj) and the item's standing (obj\_location) to the Obj Tracker. In the IoE-6G example, the Obj Tracker modules dwells in the cloud, and that implies that however in the IoE-Haze 6G case, it lives in the haze hub, Mehmood, R.; 2020).

## C.Infrastructure of the Networks

We have partitioned gadgets to five classifications: cloud, entrance, haze, edge, and sensor/actuator. As these gadgets run at different levels, the assessed association idleness between every one of them changes. Since they are thought to be important for the edge contraptions the connection inertness between the boundaries and their Sensor/Actuator is set to 1ms. To keep up with some measure of execution edges, we purposefully settled unassuming evaluations for latencies comparative with the normal 6G timings. Table 3 Configurations of link latency

Link	Latency
Cloud Gateway	99
Gateway-Fog	3
Fog-Edge	2
Edge- Sensor/Actuator	2



Fig. 3 Configurations of link latency

The network usage of electricity every hour (Eh) is determined using Equation, where the predicted consumption & U is is the network utilization. We utilized the electrical energy calculation of a gigabyte transaction in the network to estimate network energy usage (Eh) (Bibri, S.E.;2017).

...5

Energy Consuption  $E_h = 3500 \times \varepsilon$  – Table 4 Estimated energy usage of the network

Energy consumption	2019	2019	2029
Best	5.96	0.29	0.0598
Worst	15.69	1.59	0.1979
Average	21.65	1.88	0.2577



Fig. 4 Estimated energy usage of the network

Table 4 indicates their projected the use of electricity rate for wireless access networks (WAN) in 2010, 2020, and 2030. As a value, the 2020 average use of energy = 0.54 kWh/GB was utilized.

## D.Increased ACO for 6G-IoT Failure Mitigation

When seeking for the optimum path, ACO has concerns with delay convergence and low search speed. To overcome this issue, the Ant-Colony-Optimization (ACO) pheromone-update solution contains reward and punishment components.

Loop deley 
$$D_{a\varepsilon A} = \frac{\sum t_{e(i)-t_{st}}}{l} \cdot 0 < i < 1$$
 ....6

When an ant identifies the optimum path while moving, it will immediately "reward" it in line with the repercussions and return coefficient. In simple terms, the sexual hormone is raised by the corresponding value, increasing the concentration of pheromones throughout the way. If this one is longer compared with the prior path, the penalty and reward coefficients is employed to "punish" it. Traveller data (data) is gotten from a counter and passed to the Travelers Processor part by the really take a look at Information modules. The IoE-6G situation places travellers Processor in the cloud, though the IoE-Haze 6G choice spots it in mist. To direct the registration system, it takes traveller (traveller) demands from the register and asks traveller subtleties (passenger\_info\_req) from an Auth. Data Supplier. The outcome (passenger\_info\_res) can be gotten back to the Traveller Interaction module by the Auth. Data Supplier.

Subsequently, when an explorer comes at the door, their subtleties will be accessible in the mist, bringing down the hindrance's response time. The Auth. Data Provider will send the traveller's information to the proper haze hub consistently, particularly to the confirmation framework (Auth.) unit in the Door Control drive, the will be explained straightaway.

## **IV. RESULTS**

This segment will give our discoveries for the IoE-6G remembering IoE-Mist 6G situation for terms of organization usage, program circle start to finish idleness, and energy utilization for the ten designs.

In the IoE-Mist 6G circumstance, the postponement is significantly more limited than in Reconnaissance. Likewise, once the traveler's data for identification is translated into the gate fog, we can observe the value of proactive caching performed by the Smart Counter each time it registers a passenger. This ensures that authentication information is available prior to getting hold of the passenger, thereby minimizing loop delay.

## A.Experiment with Different Configurations

The number of regions, surveillance footage, meters, and palettes are the primary setup parameters for the district simulator. To depict the active areas, the number of sections is fixed at 100.

We indicate what number of cameras, yards, and bins in each region. Ten combination were also tested in this investigation. The goal here is to show how building performance changes as the complexity of IoE devices grows.

As a result, the total amount of surveillance footage, meters, and bins for area (fog device) is raised from one to ten, resulting in an aggregate amount of end devices that ranges from 300 to 2100. The sensors being used in this case scenario are set to create workloads on occasion using a foreseeable dispersion of 5 ms. Table 5 lists the qualities of all workload for the two apps that switch between program modules, while the Intelligent Security.

module	Destination	CPU	Network
Meter	M-Monitor	210	540
M- monitor	Outage Notifies	489	2560
M-M	Elect controller	1400	1409
E- controller	User interface	1490	1800
E-C	Meter ctrl	450	90
Bin	B-monitor	120	2056
B-M	Full-N	140	501
B-coord	User -ITF	1500	606
B-C	Bin ctrl	460	28

**Table 5 Configuration of Workloads in a Smart District** 





We analyzed the complete latency of three application: Smart Security, Smart Meter, and Brilliant Bin. The Intelligent The monitoring program result is shown here, but the other two programs findings are not since they share the exact same trend owing to equivalent module location. Because of the local study on the fog, every application demonstrated a substantial decrease in the end-to-end latency of the program's primary control loops.

The Smart Observation delay varied around 8 to 10 ms for the IoE-Fog-6G event in addition to six to seven s for the IoE-6G situation. Smart Meters and Intelligent Bin delay varying from 10 to 12 ms in the IoE-Fog-6G scenario and from 4 to 5 s in the IoE-6G scenario. The slight rise in latency is a result of the minute detail of IoE gadgets, which is increasing their impact on fog machines as more applications arrive at them.

## **B.Cloud Training/Retraining and Induction**

In the first DAIaaS instance, all data is routed to a server (clouds) for processing. As a result, all AI computing and analyzing modules, encompassing Data Agg., Data Fusion, to name just Data Prep., The model Establishing, and Analytics, are situated in the datacenter, with the sole exception of the collection of information module, which will be used on the edges to gather information obtained from sensors.

These modules, their setups in the two layers of networks, and the workloads that exist that exist between them can be seen as a directed graph. Table 6 summarizes the various workload traveling between units as well as the needed network and CPU horsepower. The aforementioned scenario will allow for a high level of computational and storage assets, allowing application to run accurate model on massive amounts of info at the cost of longer latency. S

Table	6 N	Vork	load	setting	in	DA	laas
-------	-----	------	------	---------	----	----	------

Work load	Source module	Destinati on	CP U	Network
Data	Sensor	Data coll.	100	RD = 50k
Coll. Data	D- Collect	Data aggregati on	200	RD
Aggregat ed data	D- aggrega ted	Data fusion	120 k	DA=RD×E
Fused data	D-fused	Data prep.	140 k	DP=DF×0. 25

Sources

Model	M= build	Analytics	400 k	1mg
Results	Analytic s	Actuator	120 k	1400

The quantity of loops differs depending on what is happening, as does the rate of each loop. A scenario contains a single loop, which is which is a triple (Data Collection, Information Aggregation, which Data Fusion, Input Preparation, Model is developing, Data analysis, and Sensor). Scenario B has two loops: one to the clouds for model building (Data Collection, Data Aggregation, Data Fusion, Data Preparation, Model creating, Build Dist. ML, Receive Diff. Model) and one to the edge with effects (Data Acquisition, Local Analysis, and Actuator).

Scenarios C and D possess three loops: one to the cloud over the building of models (Fog Collection of Data, Data Agg., Information Fusion, The information Prep., Example Building, Create Dist. ML, Get Dist. Model), another to the fog for emulate creation (Data Acquisition, Fog Data Gathering, Fog Information Agg., Fog The information Fusion, The fog Data Prep., Fog The model developing, Fog Create Dist. ML, Gain Fog Dist. Model).



Fig. 6 IaaS: Internet-based application with a database that is relational

Because of the upcoming communication connected with battery-less nodes in reflect structures, its potential use in terms of supplying huge connection in future 6G systems is strongly engaged. The discovery of crucial needs (i.e., accurate phase and channel status) at network nodes cannot be overlooked. Finally, these needs may be met with the use of non-coherent scattering interaction, which have a better potential for optimizing the allocation of resources and enhancing services across networked devices.

## V. DISCUSSION

Also, once the traveler's personal data has been translated into the gate fog, we can observe the value of preemptive caching performed by the Smart Meter when it verifies passengers. This ensures that validation knowledge is available prior to the arrival of the passenger, reducing loop delay. Finally, the typical end-to-end program loop delay for a Clever Count.

The tuple (Counter Device, Check Info, Passenger Processing, The major control system for the Intelligent Counter program includes Auth. Info Provider, Passengers Processing, which is and Counter Ctrl. Because of the manner modules are put in this application, the results differ from those of the Surveillance and Gate apps.

In both instances, the Authentication. Info Provider modules will always reside in the cloud, thus as the quantity of devices rises, so does the demand on the datacenter, resulting in longer delays.

The average the quantity of energy used for information about networks transport. The energy usage in the IoE-Fog-6G situation is decreased by roughly 3 MWh with 2160 gadgets, Muhammed, T.; 2020) [30], so this ratio is likely to grow when additional devices joined. Similarly, fog deployment lowered the cost of electricity for 2160 devices by \$3500 per day, saving approximately \$1,260,000 annually.

The smart neighborhood is the foundation of smart cities, and many different ways may be used to give a smartness and will improve people's lives. In a smart environment, fuel and utility help medical care, education, transport, disposal of trash, a sustainable environment, and many other challenges must be dealt with precision and effectively. Smart meters and Network of Things devices provide inelegant continuous tracking of the environment. Sensing such as infrared meters, ultrasonic devices, capacitive loops sensors, cameras, RFID, magnetometers, which and/or electromagnetic radar are utilized in applications ranging as parking assistance systems, parking lot surveillance, parking lot reservations, vehicle entry, and management of safety. Intelligent electrical networks might be used in energy supply as well as management systems to enable continuous monitoring and management using instruments that can read characteristics such as electrical current, voltage, electrical flow, and temperatures.

## VI. CONCLUSION

In this study, we presented and tested a methodology for DAIaaS provisioning in IoE and 6G settings employing a trio of cases encompassing eight instances, nine services and delivery models, or 50 different sensing and software elements. These case studies let us to evaluate several DAIaaS architecture options and discover operational constraints. The first two investigations simulated actual physical situations.

We were able to witness the benefits of different compute placement methods such as allowing us to cut endto-end latency, network utilization, usage of energy, and yearly cost of electricity by 99.8%, thirty-three percent, 3 MW, and 36 percent, respectively. The third case study looked into several AI ways to deliver without considering the underlying applications.

Further, we were capable of to find alternative design options that allowed us to cut down on average end-to-end latency, network capacity, electrical power consumption, and yearly costs of energy by a rate of 66%, 8 MW, and 66%. We also showed that some design decisions might result in inferior performance (e.g., larger latencies) at the expense of improved AI accuracy, and the other way around. This achievements will have a significant impact on the development of the next generation. Digital infrastructure for cleverer societies by facilitating the standardization for distributed artificial intelligence provisioning, allowing creators to focus on domain- particular details without having to worry about automated training and speculation, and by assisting in the systemization of the mass manufacturing of gadgets for smarter environments.

## **Future work**

Future work will concentrate on expanding the breadth and depth of the DAIaaS framework in terms of case studies, use, sensors, and modules of software, as well as AI delivery models, and therefore generating novel tactics, models, and perspectives for the provision of cloud-based AI services.

## VII. REFERENCES

- [1] S. Chen, Y.-C. Liang, S. Sun, S. Kang, W. Cheng, M. Peng, Vision, requirements, and technology trend of 6G: How to tackle the challenges of system coverage, capacity, user data-rate and movement speed, IEEE Wirel. Commun. 27 (2) (2020) 218–228.
- [2] M.H. Alsharif, A.H. Kelechi, M.A. Albreem, et al., Sixth generation (6G) wireless networks: Vision, research activities, challenges and potential solutions. Symmetry, Symmetry 12 (676) (2020) 4.
- [3] L.U. Khan, I. Yaqoob, M. Imran, et al., 6G wireless systems: A vision, architectural elements, and future directions, IEEE Access 8 (14) (2020) 14704–47029.
- [4] S. Basharat, S. Ali Hassan, H. Pervaiz, A. Mahmood, Z. Ding, M. Gidlund, Reconfigurable intelligent surfaces: Potentials,

applications, and challenges for 6G wireless networks, IEEE Wirel. Commun. (2021) 1–8. [6]

- [5] H. Wang, W. Wang, X. Chen, et al., Wireless Information and Energy Transfer in Interference Aware Massive MIMO Systems, IEEE Global Communications Conference, 2014.
- [6] X. You, C.-X. Wang, J. Huang, et al., Towards 6G wireless communication networks: Vision, enabling technologies, and new paradigm shifts, Sci. China Inf. Sci. 64 (1) (2021) 1–74.
- [7] V.-L. Nguyen, P.-C. Lin, B.-C. Cheng, R.-H. Hwang, Y.-D. Lin, Security and privacy for 6G: A survey on prospective technologies and challenges, IEEE Commun. Surv. Tutor. (2021) 1.
- [8] D.C. Nguyen, M. Ding, P.N. Pathirana, A. Seneviratne, J. Li, D. Niyato, O. Dobre, H.V. Poor, 6G Internet of Things: A comprehensive survey, IEEE Internet Things J. (2021) 1.
- [9] N.-N. Dao, Q.-V. Pham, N.H. Tu, T.T. Thanh, V.N.Q. Bao, D.S. Lakew, S. Cho, and Survey on aerial radio access networks: Toward a comprehensive 6G access infrastructure, IEEE Commun. Surv. Tutor. 23 (2) (2021) 1193–1225.
- [10] C.D. Alwis, A. Kalla, Q.-V. Pham, P. Kumar, K. Dev, W.-J. Hwang, M. Liyanage, Survey on 6G frontiers: Trends, applications, requirements, technologies and future research, IEEE Open J. Commun. Soc. 2 (2021) 836–886.
- [11] Qi, Q.; Chen, X.; Zhong, C.; Zhang, Z. Integration of Energy, Computation and Communication in 6G Cellular Internet of Things. IEEE Commun. Lett. 2020, 24, 1333–1337.
- [12] Liu, C.; Feng, W.; Tao, X.; Ge, N. MEC-Empowered Non-Terrestrial Network for 6G Wide-Area Time-Sensitive Internet of Things. Engineering 2022, 8, 96–107.
- [13] Padhi, P. K., & Charrua-Santos, F. (2021). 6G enabled tactile internet and cognitive internet of healthcare everything: Towards a theoretical framework. Applied System Innovation, 4(3), 66.
- [14] Zhang, L., Liang, Y. C., & Niyato, D. (2019). 6G Visions: Mobile ultra-broadband, super internet-of-things, and artificial intelligence. China Communications, 16(8), 1-14.
- [15] Mistry, Z., Kumar Yadav, A., & Kothari, M. (2021). A Review on 6th Generation Wireless Communication Networks Based on Artificial Intelligence. Innovations in Cyber Physical Systems: Select Proceedings of ICICPS 2020, 275-286.
- [16] Seng, K. P., Ang, L. M., & Ngharamike, E. (2022). Artificial intelligence Internet of Things: A new paradigm of distributed sensor networks. International Journal of Distributed Sensor Networks, 18(3), 15501477211062835.\
- [17] Gai, R., Du, X., Ma, S., Chen, N., & Gao, S. (2021, March). A Summary of 5G applications and prosprets of 5G in the Internet of Things. In 2021 IEEE 2nd International Conference on Big Data, Artificial Intelligence and Internet of Things Engineering (ICBAIE) (pp. 858-863). IEEE.
- [18] Iliev, T. B., Ivanova, E. P., Stoyanov, I. S., Mihaylov, G. Y., & Beloev, I. H. (2021, September). Artificial intelligence in wireless communications-evolution towards 6G mobile networks. In 2021 44th International Convention on Information, Communication and Electronic Technology (MIPRO) (pp. 432-437). IEEE.
- [19] Ndiaye, M., Saley, A. M., Niane, K., & Raimy, A. (2022, March). Future 6G communication networks: Typical IoT network topology and Terahertz frequency challenges and research issues. In 2022 2nd International Conference on Innovative Research in Applied Science, Engineering and Technology (IRASET) (pp. 1-5). IEEE.
- [20] Wang, Z., Du, Y., Wei, K., Han, K., Xu, X., Wei, G., ... & Su, X. (2022). Vision, application scenarios, and key technology trends for

6G mobile communications. Science China Information Sciences, 65(5), 151301.

- [21] Iannacci, J. (2021, August). The WEAF mnecosystem: A perspective of MEMS/NEMS technologies as pillars of future 6G, super-IoT and tactile internet. In 2021 IEEE International Conference on Smart Internet of Things (SmartIoT) (pp. 52-59). IEEE.
- [22] Zhang, C., & Lu, Y. (2021). Study on artificial intelligence: The state of the art and future prospects. Journal of Industrial Information Integration, 23, 100224.
- [23] Nazar, M.J.; Alhudhaif, A.; Qureshi, K.N.; Iqbal, S.; Jeon, G. Signature and flow statistics based anomaly detection system in software-defined networking for 6G internet of things network. Int. J. Syst. Assur. Eng. Manag. 2023, 14, 87–97.
- [24] Li, Q.; Xiao, R. The use of data mining technology in agricultural e-commerce under the background of 6G Internet of things communication. Int. J. Syst. Assur. Eng. Manag. 2021, 12, 813–823.
- [25] Qi, F.; Li, W.; Yu, P.; Feng, L.; Zhou, F. Deep learning-based BackCom multiple beamforming for 6G UAV IoT networks. EURASIP J. Wirel. Commun. Netw. 2021, 2021, 50.
- [26] Lyu, B.; He, M. The application of artificial intelligence technology of 6G internet of things communication combined with drama language art. Int. J. Syst. Assur. Eng. Manag. 2021, 12, 864–870.
- [27] Yigitcanlar, T.; Butler, L.; Windle, E.; DeSouza, K.C.; Mehmood, R.; Corchado, J.M. Can Building "Artificially Intelligent Cities" Safeguard Humanity from Natural Disasters, Pandemics, and Other Catastrophes? An Urban Scholar's Perspective. Sensors 2020, 20, 2988.
- [28] Mehmood, R.; See, S.; Katib, I.; Chlamtac, I. Smart Infrastructure and Applications: Foundations for Smarter Cities and Societies. In EAI/Springer Innovations in Communication and Computing; Springer International Publishing: New York, NY, USA; Springer Nature Switzerland AG: Cham, Switzerland, 2020; p. 692.
- [29] Bibri, S.E.; Krogstie, J. The core enabling technologies of big data analytics and context-aware computing for smart sustainable cities: A review and synthesis. J. Big Data 2017, 4, 1–50.
- [30] Muhammed, T.; Albeshri, A.; Katib, I.; Mehmood, R. UbiPriSEQ: Deep Reinforcement Learning to Manage Privacy, Security, Energy, and QoS in 5G IoT HetNets. Appl. Sci. 2020, 10, 7120.



Hamza ali al shawabkeh I'm currently working as an Assistant Professor in the College of Computing and Information, at Al-Baha University, Saudi Arabia Since May 2013. I completed my PhD in Engineering Sciences (Aided structural synthesis of microelectromechanical systems and their dynamics analysis )from Lviv Polytechnic National University in 2011. I completed

my MSc in Telecommunication systems and Networks, at Donetsk National University of Ukraine in 2007. I obtained my B.Sc. in Telecommunication systems and Networks -Donetsk National University of Ukraine. in 2005. Over 12 years of professional work experience in the Information Technology industry and academia, My research interests are in information technology and Telecommunication systems and Networks, and I love working in community service. I have worked in many skills development courses, and I find myself in the process of teaching and communicating information to students and researches.